

# VA1903wmb

## 19" VALUE SERIES WIDESCREEN LCD

WITH 5MS VIDEO RESPONSE

## Expansive desktop performance.

ViewSonic's 19" VA1903wmb LCD brings spacious widescreen performance to the desktop at an affordable price. The widescreen aspect ratio and high 1440x900 resolution make it easy to view and work in multiple documents and applications at the same time. FAST CLEARMOTIV® 5MS VIDEO RESPONSE, 800:1 contrast ratio (typ) and 300-nit brightness (typ) deliver IMMERSIVE GAMING with no blurs or ghosting, extreme clarity, intense color and brightness. The VA1903wmb delivers on ViewSonic's tradition of BRILLIANT IMAGE QUALITY AND RELIABLE PERFORMANCE all at a budget-friendly price. It's the right choice for gamers, home/small office users and corporate professionals.



### ENHANCE YOUR WORK AND PLAY.

- > **Fast 5ms video response** delivers superior picture clarity
- > **1440x900 native resolution**  
Incredible image detail for sharp text and graphics.
- > **High brightness and contrast ratio**  
300-nit brightness (typ) and 800:1 contrast ratio (typ) for rich, detailed images.
- > **Multimedia enhanced**  
Save desk and workspace and enjoy rich, stereo sound with built-in stereo speakers.
- > **Stylish slim-bezel design**  
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **Full 19" viewable widescreen**  
Displays a full, flat 19" viewable area with crisp detail and fully saturated color.
- > **OSD/power lock secures your settings**  
Prevents changes to monitor settings and maintain an optimized image.
- > **OnView® controls for superior screen adjustability**  
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **Integrated power supply**
- > **PC and Mac compatible**
- > **TCO '03 and ENERGY STAR® qualified**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference® 

# VA1903wmb

19" VALUE SERIES LCD WITH 5MS VIDEO RESPONSE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [13847-00B-01/08] VA1903mb-1

<b>LCD</b>	Type	19" color TFT active matrix WXGA+ LCD
	Display Area	16.1" horizontal x 10.0" vertical; 19.0" diagonal
	Optimum Resolution	1440x900
	Contrast Ratio	800:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 5:1
	Response Time	5ms (typ)
	Light Source	Long life 50,000 hrs (typ)
	Brightness	300 cd/m <sup>2</sup> (typ)
	Aspect Ratio	16:10
	Panel Surface	Anti-glare
<b>VIDEO INPUT</b>	Analog	RGB analog (75 ohms, 0.7 Vp-p)
	Frequency	F <sub>H</sub> : 24~82kHz, F <sub>V</sub> : 50~75Hz
	Sync	H/V separated (TTL),
<b>COMPATIBILITY</b>	PC	VGA up to 1440x900 non-interlaced
	Mac®*	Power Mac™ G3/G4/G5 up to 1440x900
<b>CONNECTOR</b>	Analog	15-pin mini D-sub
	Power	3-pin AC plug (CEE22)
	Audio	Stereo mini jack
<b>AUDIO</b>	Speakers	2x1.5-watt
	Amplifier	2x1-watt
<b>POWER</b>	Voltage	AC 100~240V, (universal), 50~60Hz (auto switch)
	Consumption	34W (typ)
<b>CONTROLS</b>	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, brightness, contrast, ViewMatch® color adjust (sRGB, 9300K, 6500K, – default, 5400K RGB), information (resolution, H-freq, V-freq, pixel clock, model number, serial nuber, web site), manual image adjust (H. size, H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
<b>OPERATING CONDITIONS</b>	Temperature	32~104°F (0~40°C)
	Humidity	10~90% (non-condensing)
<b>DIMENSIONS</b>	Physical with stand	17.6" x 15.9" x 8.3" (448mm x 403mm x 210mm)
	Physical without stand	17.6" x 12.5" x 2.5" (448mm x 318mm x 63mm)
	Net with stand	10.4 lb. (4.7 kg)
	Net without stand	9.7 lb. (4.3 kg)
	Gross with stand	13.2 lb. (6.0 kg)
<b>REGULATIONS</b>	UL, cUL, FCC-B, CB, CE, NOM, TUV/GS, TUV/ERGO (covers ISO13406-2), TCO'03, BSMI, CCC, ENERGY STAR®, PSB, C-TICK, RoHS, WEEE, VCCI, GOST-R, SASO	
<b>RECYCLE/DISPOSAL</b>	The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws	
<b>POWER MANAGEMENT</b>	Meets TCO'03 and ENERGY STAR® standards	
<b>PACKAGE CONTENTS</b>	LCD display, video cable, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD	
<b>WARRANTY</b>	Three-year limited warranty on parts, labor and backlight.	

**ViewSonic®**  
See the difference® 

For more product information, visit us on the web at ViewSonic.com